## **Electrolux Benefit Cabinets**

## Digital freezers - 1300 lt

The range consists of 5 fan assisted models of 1300 litres refrigeration cabinets that offer excellent standards in terms of performance and efficiency. These models come in freezer version with a choice of materials (304 AISI, 430 AISI or white painted steel) and are available with full doors.



726464

- Internal and external structure in 304 AISI, 430 AISI or white painted steel, top and back in galvanized steel. 150 mm high -adjustable feet.
- Digital control panel allowing the easy and precise setting and control of the internal temperature.
- Completely automatic defrosting and automatic evaporation of defrost water (304 AISI models), manual emptying of defrost water (430 AISI models).
- High standards of hygiene and ease of cleaning are guaranteed by the rounded internal corners of the cabinet and easily removable runners and grids (without the use of tools).
- The refrigeration unit can operate in tropical climates (+43°C ambient temperature).
- · Excellent forced air cooling system that ensures the utmost uniformity of temperature in the cabinet and guarantees a perfect storage quality of the goods.
- High-density expanded polyurethane insulating foam, 60 mm in thickness, with cyclopenthane injection, guarantees exceptional, long-term insulation and notable energy savings.
- The rational use of the internal space of the refrigerator guarantees a large storage area suitable to contain 2/1 GN grids.







- Self-closing door, positioned in less than 90°, with a stop at 95° and a maximum opening at 180°, equipped with a magnetic door seal to guarantee perfect closure.
- The pressed stainless steel recessed door handle without joints makes opening the cabinet extremely easy. All the doors are fitted as standard with locks and keys and a microswitch to switch off the fan when the door is opened.
- Stainless steel feet (plastic interior).
- A wide range of optional accessories are available.
- CFC and HCFC free.
- All models comply with the standards required by the main international approval bodies and are H marked.


•	L	•	

-5008

Subject to change without notice

	RS13FX42F 726464	RS13FX2F 726323	RS13FW2F 726476	RS13F32F 726468	RS13FX4H 727158
TECHNICAL DATA					
Operating temperature - min/max °C	-22/-15	-22/-15	-22/-15	-22/-15	-22/-15
Operating mode	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
Type of stainless steel					
external	Stainless Steel	304 AISI	Prepainted Steel	304 AISI	Stainless Steel AISI 304 Scotch Brite
internal	Stainless Steel	304 AISI	Stainless Steel	304 AISI	Stainless Steel AISI 304 Scotch Brite
Gross capacity (D.I.N. 8952) - I.	1300	1300		1300	1300
External dimensions - mm					
width	1440	1440	1440	1440	1440
depth/with open doors	788, 1440	788, 1440	788, 1440	788, 1440	788, 1450
height	2000	2000	2000	2000	2000
N° and type of door	2	2	2	2	4x1/2
Door hinges	1 Left+1 Right	1 Left+1 Right	1 Left+1 Right	1 Left+1 Right	2 Left+2 Right
N° and type of grids (included)	6, GN 2/1	6, GN 2/1	6, GN 2/1	6, GN 2/1	8, GN 2/1
N° defrost in 24 hrs.	4/30'	4/30'	4/30'	4/30'	4/30'
Refrigerant type	R404a	R404a	R404a	R404a	R404a
Refrigerant quantity - g.	450	450	450	450	450
Refrigeration power - W	962	962	962	962	962
Power - kW					
installed-electric	1.008	1.008	1.008	1.008	1.008
Internal light				•	
Net weight - kg.	247	247	247	247	247
Power supply - V, phases, Hz	230 V, 1, 50	230 V, 1, 50	230 V, 1, 50	230 V, 1, 50	230 V, 1, 50

	RS13FX42F 726464	RS13FX2F 726323	RS13FW2F 726476	RS13F32F 726468	RS13FX4H 727158
INCLUDED ACCESSORIES					
2 S/S RUNNERS FOR 600-650/1300-1400L.REF	6	6	6	6	
2 S/S SIDE RUNNERS FOR 600-1300L REFRIG.					8
2/1 GN GREY "RILSAN" GRID	6	6	6	6	8
ACCESSORIES					
2 S/S RUNNERS FOR 600-650/1300-1400L.REF	881456	881456	881456	881456	
2 S/S SIDE RUNNERS FOR 600-1300L REFRIG.					880557
2 WHEELS FOR REFRIGERATORS/REFRIG.TABLES	880539	880539	880539	880539	880539
2/1 GN AISI 304 S/S GRID	881067	881067		881067	881067
2/1 GN GREY "RILSAN" GRID	880720	880720	880720	880720	880720
3 RILSAN CENTR.GRIDS-2 DOOR REF/FREEZERS	880211	880211	880211	880211	
ENERGY FREE ALARM DEVICE	881089	881089	881089		881089
KIT HACCP EKIS	922166	922166	922166	922166	922166
KIT INTEGRATED HACCP-DIG. REFR. (IR33)	880205	880205	880205	880205	880205
KIT TO FIT 11 PASTRY TRAYS (400X600 MM)	881031	881031	881031	881031	881031
MEAT RAIL FOR 650-1400 L REFRIGERATORS	881451	881451	881451	881451	
PRINTER FOR HACCP BASIC VERSION REFRIG.	881457	881457	881457	881457	881457



	RS13FX42F 726464	RS13FX2F 726323	RS13FW2F 726476	RS13F32F 726468
LEGEND				
EI - Electrical connection	230 V, 1, 50	230 V, 1, 50	230 V, 1, 50	230 V, 1, 50